

Europäisches Patentamt

European Patent Office

Office européen des brevets



(11) EP 0 929 143 A3

(12)

EUROPEAN PATENT APPLICATION

(88) Date of publication A3: 29.03.2000 Bulletin 2000/13

(51) Int. Cl.⁷: **H02M 3/158**

(43) Date of publication A2: 14.07.1999 Bulletin 1999/28

(21) Application number: 98120647.7

(22) Date of filing: 03.11.1998

(84) Designated Contracting States:

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU

MC NL PT SE

Designated Extension States:

AL LT LV MK RO SI

(30) Priority: 12.01.1998 JP 361598

(71) Applicant:
NIHON PROTECTOR CO., LTD.
Amagasaki-shi, Hyogo 660-0805 (JP)


(72) Inventor: Sakai, Setsuo c/o Nihon Protector Co., Ltd. Amagasaki-shi, Hyogo 660-0805 (JP)

(74) Representative: VOSSIUS & PARTNER Slebertstrasse 4 81675 München (DE)

(54) Switching regulator

(57) A switching regulator includes: a boost chopper circuit A including a plurality of inductances (2, 3, 4 and 5) which are connected in parallel with a D.C. power supply (1) for boosting the D.C. power supply (1), a plurality of commutating diodes (6, 7, 8 and 9) which are connected to output sides of those inductances (2, 3, 4 and 5), respectively, a plurality of switching elements (10, 11, 12 and 13) for connecting the D.C. power supply (1) and nodes between the respective inductances (2 to 5) and the respective diodes (6 to 9) in a short-

circuiting manner, and a smoothing capacitor (14) connected in series to a combined output section of those diodes (6 to 9); a control circuit (15) for controlling the on/off operation of those switching elements (10 to 13); and a load (16) connected in parallel with the smoothing capacitor (14). The plurality of switching elements (10 to 13) repeatedly operate while the operation of the plurality of switching elements (10 to 13) is sequentially delayed by a predetermined period of time.



Printed by Xerox (UK) Business Services 2.16.7/3.6



EUROPEAN SEARCH REPORT

Application Number

EP 98 12 0647

Category	Citation of document with indication, where appropriate, of relevant passages		Relevant to claim	CLASSIFICATION OF THE APPLICATION (Intcl.6) H02M3/158
X	US 4 972 292 A (PET	1-3		
Y	20 November 1990 (1 * column 5, line 59 figures 1,4 *	4		
X	US 5 278 489 A (BOW 11 January 1994 (19 * column 2, line 65 figure 1 *	VERS MARK C) 194-01-11) 5 - column 3, line 25;	1,2	
Y	EP 0 503 715 A (PHI 16 September 1992 (* figure 1 *	LIPS NV) 1992-09-16)	4	
:				TECHNICAL FIELDS
		·		HO2M
	·			
	The present search report has	been drawn up for all claims	_	
	Place of search	Date of completion of the search		Examiner
	THE HAGUE	4 February 200	9 Gen	tili, L
X : part Y : part door A : tech	ATEGORY OF CITED DOCUMENTS ioutarly relevant if taken alone ioutarly relevant if combined with anot ment of the same category who pois background - written disclosure	E : earlier patent after the filing her D : document ob L : document obs	ed in the application ed for other regsons	ihed on, or

ANNEX TO THE EUROPEAN SEARCH REPORT ON EUROPEAN PATENT APPLICATION NO.

EP 98 12 0647

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

04-02-2000

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 4972292	Α	20-11-1990	NONE	
US 5278489	Α	11-01-1994	NONE	
EP 0503715	A	16-09-1992	NL 9100445 A DE 69206020 D DE 69206020 T JP 5111259 A US 5272613 A	01-10-199 21-12-199 30-05-199 30-04-199 21-12-199
		·		

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

3

DE19837639

Publication Title:

Converter overload protection circuit

Abstract:

Abstract of DE19837639

An overload protection circuit includes a first converter (UM1) and a second converter (UM2) connected to the first in a chain circuit, in which the first converter (UM1) has a first switching transistor to control the output voltage (UAO), and the second converter (UM2) includes a transformer (Tr) with associated rectifier unit (GR) for rectifying the transformer (Tr) secondary voltage. A decision unit (SE) controls the load current path (SD) of the first switching transistor (T1), in which current and voltage value detected at the output of the first converter (UM1) are determined and then supplied to the decision unit (SE). When safe forced tripping of the switching elements (G1,G2) in the rectifying unit (GR) is no longer possible, the first switching transistor (T1) is driven to make the load current path high- resistance.

Data supplied from the esp@cenet database - Worldwide

Courtesy of http://v3.espacenet.com

This Patent PDF Generated by Patent Fetcher(TM), a service of Stroke of Color, Inc.